



SP60 Pump

for Pool-Krete® Premix



Specifically designed for pumping Pool-Krete® Premix and is Intended for use with the CM-1 Continuous Mixer for Pool-Krete® Premix. When used with the Continuous Mixer, can pump up to 36 bags of Pool-Krete® Premix per hour. Sold separately from the Continuous Mixer. Parts and hoses sold separately.

The Strong Company, Inc.
4505 Emmett Sanders Road | Pine Bluff, AR 71601
Toll Free (800) 982-8009
(870) 535-7617 | Fax (870) 850-6933
Email: info@strongseal.com | www.strongseal.com

*Strong Manufacturing Co. manufactures this machine
for The Strong Company Inc.*



Engine

Industrial rated gasoline engine equipped with recoil start and low oil shut down safety system.
Approximately 2 hours run time on one tank of fuel.

Material Pump

#60 progressive cavity design pump, chrome rotor, natural rubber stator, 5 cubic feet wet material holding hopper, variable output of 0-10 gpm @10 psi.
Options: Carbide rotor, UHMW liner for hopper, material hose pressure gauge

Hydraulic System

Fixed displacement hydraulic pump, 10-gallon hydraulic reservoir, variable speed directional control valve.

Frame

Lightweight frame constructed from low carbon steel, equipped with removeable transport handles and pneumatic wheels for ease of placement.

Dimensions

Length: 6', Width: 2' 2", Height: 3' 1",
Weight: 550 lb.