



Strong-Seal® MiniMate II

The Complete Solution for Small Mixing and Pumping Jobs

Completely mobile, all components are mounted on a four-wheel frame that can be rolled into easements. The Strong-Seal® MiniMate II is a dependable, efficient machine for the installation of cementitious material to rehabilitate municipal concrete and masonry structures.

The Strong Company, Inc.
4505 Emmett Sanders Road | Pine Bluff, AR 71601
Toll Free (800) 982-8009
(870) 535-7617 | Fax (870) 850-6933
Email: info@strongseal.com | www.strongseal.com

Strong Manufacturing Co. manufactures this machine
for The Strong Company Inc.

Dimensions

Length: 6' 6", Width: 3' 2", Height: 4' 4",
Weight: 750 lb.



Engine

Honda, 8hp, gasoline, air-cooled.
Options: Contact The Strong Company, Inc. for other engine options.

Mixer

Patented 2.5 cubic feet double-drum mixer, variable speed, hydraulically operated via mechanical drive, counter rotating ribbon paddles, rubber-lined.
Options: Adjustable packing chambers and outboard bearings

Material Pump

#60 progressive cavity design pump, material hose pressure gauge, chrome rotor, natural rubber stator, 2.5 cubic feet wet material holding hopper, variable output 0-5 gpm @ 0 psi.
Options: Carbon-coated rotor, UHMW liner for hopper

Water System

Direct inline analog water meter.
Options: Contract The Strong Company, Inc.

Hydraulic System

Fixed displacement hydraulic pump, 10-gallon hydraulic reservoir.

Air System

Jenny GCU air compressor.

Frame

Lightweight frame constructed from low carbon steel, equipped with non-marking pneumatic wheels for ease of placement.