

T H E
Strong Company
I N C .

Strong-Seal® MiniMate

*The Complete Solution for
Small Mixing and Pumping Jobs*

Completely mobile, all components are mounted on a four-wheel frame that can be rolled into easements. The Strong-Seal® MiniMate is a dependable, efficient machine for the installation of cementitious material to rehabilitate municipal concrete and masonry structures.

The Strong Company, Inc.
4505 Emmett Sanders Road | Pine Bluff, AR 71601
Toll Free (800) 982-8009
(870) 535-7617 | Fax (870) 850-6933
Email: info@strongseal.com | www.strongseal.com



Engine

8HP industrial rated gasoline engine equipped with recoil start and safety shut down system. Approximately 2 hours run time on one tank of fuel.
Options: Contact The Strong Company, Inc. for other engine options.

Mixer

Patented contra-blend design, 2.5 cubic foot capacity, twin ribbon paddles with wiper blades, packing type seal chambers and support bearings on all shafts. Body constructed of twin, interconnected, horizontal drums. Mixer empties without tilting.
Options include adjustable packing with outboard bearings. Rubber or UHMW lining.

Material Pump

#60 progressive cavity design pump, material hose pressure gauge, chrome rotor, natural rubber stator, 2.5 cubic feet wet material holding hopper, variable output 0-5 gpm @ 0 psi.
Options: Carbon-coated rotor, UHMW liner for hopper, material hose pressure gauge.

Water System

Direct inline analog water meter.
Options: Contact The Strong Company, Inc.

Hydraulic System

Fixed displacement hydraulic pump, 10-gallon hydraulic oil reservoir.

Air System

Contact The Strong Company, Inc. for air system options.

Frame

Lightweight frame constructed from low carbon steel, equipped with non-marking pneumatic wheels for ease of placement.

Dimensions

Length: 6' 6", Width: 3' 2", Height: 4' 4",
Weight: 750 lb.

Strong Manufacturing Co. manufactures this machine for The Strong Company Inc.