



## Strong-Seal® 35C-4 SprayMate®

The Complete Solution for Mixing and Pumping

Completely mobile, all components are mounted on a tandem axle trailer and can be towed with a pick-up truck. The Strong-Seal® 35C-4 SprayMate® is a dependable, efficient machine for the installation of cementitious material to rehabilitate municipal concrete and masonry structures.



The Strong Company, Inc.  
4505 Emmett Sanders Road | Pine Bluff, AR 71601  
Toll Free (800) 982-8009  
(870) 535-7617 | Fax (870) 850-6933  
Email: [info@strongseal.com](mailto:info@strongseal.com)  
[www.strongseal.com](http://www.strongseal.com)

Strong Manufacturing Co. manufactures this machine  
for The Strong Company Inc.

### Engine

Yanmar 63HP, industrial, water-cooled diesel engine.

*Options: Contact The Strong Company, Inc.*

### Mixer

Patented 5 cubic feet double-drum mixer, variable speed, hydraulically operated via mechanical drive, counter rotating ribbon paddles, rubber-lined.

*Options: Adjustable packing chambers and outboard bearings, hydraulically operated mixer door, UHMW liner*

### Material Pump

#60 progressive cavity design pump, material hose pressure gauge, chrome rotor, natural rubber stator, 2.5 cubic feet wet material holding hopper, variable output 0-8 gpm @ 0 psi.

*Options: Carbide rotor, 6 cubic ft material blender, UHMW liner for hopper*

### Water System

200-gal water tank, belt driven water pump, analog water meter.

*Options: Hydraulic powered high-pressure washer, digital water meter*

### Hydraulic System

Variable displacement pressure compensated piston pump with fixed displacement gear pump, 30-gal hydraulic oil reservoir.

*Options: Hydraulic air cooler*

### Air System

Jenny GCU air compressor, belt driven, 27 cfm displacement, 24 cfm free air @ 100 psi.

*Options: Contact The Strong Company, Inc. for optional compressors.*

### Frame

Made of tubular steel, tandem axle, 14" tires, slipper spring suspension, electric brakes, running lights, ball or pintle hitch.

*Options: Contact The Strong Company, Inc.*

### Dimensions

Length: 16'

Width: 6' 3"

Height: 6' 6"

Weight: 4,500 lb.