



Strong-Seal® SprayMate® 35D

The Complete Solution for Mixing and Pumping

Completely mobile, all components are mounted on a tandem axle trailer and can be towed with a pick-up truck. The Strong-Seal® SprayMate® 35D is a dependable, efficient machine for the installation of cementitious material to rehabilitate municipal concrete and masonry structures.



The Strong Company, Inc.
4505 Emmett Sanders Road | Pine Bluff, AR 71601
Toll Free (800) 982-8009
(870) 535-7617 | Fax (870) 850-6933
Email: info@strongseal.com
www.strongseal.com

Strong Manufacturing Co. manufactures this machine
for The Strong Company Inc.

Engine

Deutz, 30hp, diesel, air-cooled.
Options: Contact The Strong Company, Inc. for other engine options.

Mixer

Patented 5 cubic feet double-drum mixer, variable speed, hydraulically operated via mechanical drive, counter rotating ribbon paddles, rubber-lined.
Options: Adjustable packing chambers and outboard bearings, hydraulically operated mixer door, UHMW liner

Material Pump

#60 progressive cavity design pump, material hose pressure gauge, chrome rotor, natural rubber stator, 2.5 cubic feet wet material holding hopper, variable output 0-8 gpm @ 0 psi.
Options: Carbide rotor, 6 cubic ft material blender, UHMW liner for hopper

Water System

200-gal water tank, belt driven water pump, analog water meter.
Options: Hydraulic powered high-pressure washer, digital water meter

Hydraulic System

Variable displacement pressure compensated piston pump with fixed displacement gear pump, 30-gal hydraulic oil reservoir.
Options: Hydraulic air cooler

Air System

Jenny GCU air compressor, belt driven, 27 cfm displacement, 24 cfm free air @ 100 psi.
Options: Contact The Strong Company, Inc. for optional compressors.

Frame

Made of tubular steel, tandem axle, 15" tires, slipper spring suspension, electric brakes, running lights, ball or pintle hitch.
Options: Contact The Strong Company, Inc.

Dimensions

Length: 18'
Width: 8' 2"
Height: 8'
Weight: 5,600 lb.