

T H E

# Strong Company

I N C .

## Strong-Seal® SprayMate® 35C

The Complete Solution for Mixing and Pumping

Completely mobile, all components are mounted on a tandem axle trailer and can be towed with a pick-up truck. The Strong-Seal® SprayMate® 35C is a dependable, efficient machine for the installation of cementitious material to rehabilitate municipal concrete and masonry structures.



### Engine

30 HP, 3 cylinder air cooled diesel engine driving hydraulic pump and air compressor.  
*Options: Contact The Strong Company, Inc. for other engine options.*

### Mixer

Contrablend design, twin ribbon paddles with Neoprene wiper blades, slurry seal packing support bearings on all shafts. Mixer to empty without tilting. Body construction of twin interconnected horizontal positioned mild steel drum, capacity 5 cubic feet.

### Material Pump

Optimized #60 full progressive cavity pump with holding hopper. Discharge rate variable from 0-8 GPM.

### Water System

1" water meter with direct reading dial, manual on-off, hydraulic driven transfer water pump complete with on-off control valve, 200 gallon storage tank.

### Control System

Hydraulic system to allow for variable speed control of mixer and pump. Includes on/off function for mixer and on/off/reverse function for pump. Also includes all necessary safety valves and controls.

### Air System

Jenny GCU air compressor, complete with air reservoir, filter, safety valve and pressure gauge.

### Frame

Dual 3,500 lb. capacity axles and slipper springs and 14" radial tires. Brakes, running lights and all components mounted to trailer.

### Dimensions

Length: 16'  
Width: 6' 3"  
Height: 6' 6"  
Weight: 4,500 lb.

The Strong Company, Inc.  
4505 Emmett Sanders Road | Pine Bluff, AR 71601  
Toll Free (800) 982-8009  
(870) 535-7617 | Fax (870) 850-6933  
Email: [info@strongseal.com](mailto:info@strongseal.com)  
[www.strongseal.com](http://www.strongseal.com)

*Strong Manufacturing Co. manufactures this machine  
for The Strong Company Inc.*