

T H E
Strong Company
I N C .

Strong-Seal®
SprayMate® 35D

The Complete Solution for Mixing and Pumping

Completely mobile, all components are mounted on a tandem axle trailer and can be towed with a pick-up truck. The Strong-Seal® SprayMate® 35D is a dependable, efficient machine for the installation of cementitious material to rehabilitate municipal concrete and masonry structures.



The Strong Company, Inc.
4505 Emmett Sanders Road | Pine Bluff, AR 71601
Toll Free (800) 982-8009
(870) 535-7617 | Fax (870) 850-6933
Email: info@strongseal.com
www.strongseal.com

Dimensions

Length: 22'
Width: 8'
Height: 8'
Weight: 5,600 lb.

Engine

Tier 4 final industrial diesel engine, complete with safety switches, hour meter and tachometer, engine cowling with replaceable air filter, 12 volt dc electric start.

Mixer

Patented Contra-blend design, 8 cubic foot capacity, twin ribbon paddles with wiper blades, packing type seal chambers and support bearings on all shafts. Body constructed of twin, interconnected, horizontal drums. Mixer empties without tilting.

Material Pump

#60 progressive cavity design pump, material hose pressure gauge, chrome rotor, natural rubber stator, 2.5 cubic feet wet material blender, variable output 0-10 gpm with pressures up to 350 psi.

Water System

Water storage tank with automatic fill valve, manual discharge valve.
Options include, Hydraulic or PTO powered Water Pump, Digital Water Meter with manual reset.

Hydraulic System

Variable displacement pressure compensated hydraulic pump variable speed directional control valves, 30 gallon hydraulic oil reservoir.

Air System

Air Compressor capable of producing up to 27cfm@90psi.

Frame

Made of tubular steel, 7,000 lb torsion axle with 19.5' radial tires, electric brakes, safety chains and breakaway switch, all required lighting, pintle, 2" ball & socket hitch.

Options: Contact The Strong Company, Inc.

Strong Manufacturing Co. manufactures this machine for The Strong Company Inc.